

DEVICE FOR DETECTING SLOPE OF VEHICLE OR THE LIKE

BACKGROUND OF THE INVENTION

5 This invention relates to a device for detecting slope of the vehicles such as a car, train or the like.

 In order to detect whether the moving object such as the car, train or the like passed through the sloped road to the two-level crossing especially, the acceleration sensor of one axis is used and detected by the conventional car
10 navigation.

 Therefore, although the acceleration sensor correctly detects the slope with the moving objects such as the conventional car and a train during running the vehicles at a constant speed, the slope cannot be measured correctly since acceleration followed in acceleration-deceleration.

15

SUMMARY OF HE INVENTION

 Accordingly, it is an object of the invention to provide a device that can detect the slope of vehicle or the like in acceleration-deceleration as well as during
20 running the vehicles at a constant speed.

 Novel features which are believed to be characteristic of the invention, both as to its organization and method of operation, together with further objects and advantages thereof, are described below with reference to the accompanying drawings in which preferred embodiments of the invention are illustrated as an
25 example.

 It is to be expressly understood, however, that the drawings are for the

purpose of illustration and description only, and are not intended as a definition of the limits of the invention.

BRIEF DESCRIPTION OF THE DRAWINGS

5

Fig.1 is a schematic diagram of the first embodiment of the present invention;

Fig.2 is an example of the first embodiment;

Fig.3 is a block diagram illustrating the first embodiment;

10 Fig.4 is an example of a formula for a calculation table illustrating the first embodiment;

Fig.5 is an example of the second embodiment;

Fig.6 is a block diagram illustrating the second embodiment;

Fig.7 is a an example of the third embodiment; and

15 Fig.8 is a block diagram illustrating the third embodiment.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

20 Preferred embodiments of the present invention are described in more detail below with reference to the accompanying drawings.

An understanding of the present invention may be best gained by reference to Figs. 1 - 4. Figs. 1 - 4 illustrate a device for detecting slope of the vehicles in accordance with a first embodiment of the present invention. Reference numeral 1 shows the device for detecting the slope, the device attached in the moving object
25 including a car, a motorcycle, train or the like.

The slope detecting device 1 is comprised of a first acceleration sensor 3 as a

horizontal detecting means to detect the acceleration of the running direction of the moving object 2; a second acceleration sensor 4 as a perpendicular detecting means to detect perpendicular acceleration to the running direction of the first acceleration sensor 3; means 5 for detecting, attaching relatively to the first acceleration sensor 3 and second acceleration sensor 4, detecting the acceleration-deceleration the moving object 2 by whether the sum of squares respectively which the acceleration detected by the first acceleration sensor 3 and the acceleration detected by the second acceleration sensor 4 is equal to the second power of gravity acceleration, and calculating the slope of the moving object in acceleration-deceleration.

Although the first and the second acceleration sensors 3 and 4 are used for the same acceleration sensor as usual in this embodiment, it should just be a sensor that can detect acceleration and gravity efficiently.

Moreover, the attachment position of the first and the second acceleration sensors 3 and 4 is attached suitably and relatively to the control part installed in the moving object 2. In this case, they are attached through wiring, and they may be used by a radio system.

The detecting means 5 is attached relatively and suitably through wiring to the control part X installed in the moving object 2 as the first and second acceleration sensors 3 and 4. Also it may be used by a radio system.

Moreover, the detecting means 5 includes a calculation table 6 which detects the acceleration-deceleration the moving object 2 by whether the sum of squares respectively which the acceleration detected by the first acceleration sensor 3 and the acceleration detected by the second acceleration sensor 4 is equal to the second power of gravity acceleration, and calculating the slope of the moving object in acceleration-deceleration.

The formula that constitutes this calculation table is explained in Fig. 4.

In Fig.4, A_H shows the horizontal acceleration of the moving object 2 (acceleration detected by the first acceleration sensor 3); A_V shows the perpendicular acceleration of the moving object 2 (acceleration detected by the second acceleration sensor 4); and A_T shows the synthetic acceleration of A_H and A_V .

Since only gravity acceleration add to the acceleration sensor when the moving object 2 is carrying out uniform operation, the related formula is formed as below:

$$A_G^2 = A_H^2 + A_V^2$$

Here, A_G shows the gravity acceleration.

Then, the slope θ of the moving object 2 is:

$$\theta = \text{TAN}^{-1}(A_H / A_V)$$

Next, during the moving object 2 runs in acceleration-deceleration, the formula is formed as below:

$$A_G^2 \neq A_H^2 + A_V^2$$

However, the perpendicular acceleration A_V of the moving object 2 is not influenced of the acceleration accompanying acceleration-deceleration of the moving object.

Therefore, the slope of the moving object 2 is calculated as below:

$$\theta = \text{COS}^{-1}(A_H / A_G)$$

Also the acceleration A_C accompanying acceleration-deceleration of the moving object at this time is calculated by:

$$A_C = A_H - (A_G^2 - A_V^2)^{1/2}$$

By using the slope calculation table 6, the slope can be calculated by the acceleration detected by the first acceleration sensor 3 and the acceleration

detected the second acceleration sensor 4 of the second detected and also the under uniform operation, and the acceleration in acceleration-deceleration.

In addition, in this embodiment, the detecting means 5 is explained that it is installed separately in the control part X as the car-mounted computer which controls the fuel injection, timing, etc mounted on the moving object 2. In addition, the detecting means 5 may be installed in the control part X integrally.

Therefore, it can be installed into the GPS, car-mounted computer and the like as usual.

The slope detection equipment 1 of the above-mentioned composition detects the slope of the moving object 2 by the first acceleration sensor 3 that detects the horizontal acceleration in uniform operation.

When the moving object 2 passes through the road with the degree of slant, two-level crossing, etc., the speed of the moving object is accelerated or decelerated. In this case, the first acceleration sensor 3 detects the acceleration of the run direction, and the second acceleration sensor 4 detects the perpendicular acceleration to the run direction.

The slope of the moving object 2 can be correctly detected through the slope calculation table 6 of the detecting means 5 based on the detected acceleration so that the slope of the moving object 2 is correctly measured corresponding to the acceleration-deceleration during it passes through the two-level crossing etc. for example.

Other embodiments of the present invention will now be described with reference to Figs. 5 - 8. In Figs. 5 - 8, the same components as in the first embodiment described above with reference to Figs. 5 - 8 are designated by the same reference numerals and therefore will not be further explained in great detail.

A second embodiment of the present invention is shown in Figs. 5 and 6. It is distinguished from the first embodiment in that means 7 for detecting is used, and the detecting means 7 includes the first acceleration sensor 3 as a horizontal detecting means to detect the acceleration of the running direction of the moving object 2; the second acceleration sensor 4 as a perpendicular detecting means to detect perpendicular acceleration to the running direction of the first acceleration sensor 3, provided at the first acceleration sensor 3 integrally. A device for detecting slope of the vehicles 1A according to the second embodiment has similar advantages to that according to the first embodiment and the installation space can be reduce.

In addition, one acceleration sensor that can detect a horizontal acceleration and perpendicular acceleration may be used.

A third embodiment of the present invention is shown in Figs. 7 and 8. It is distinguished from the second embodiment in that a detecting means 7A including the second acceleration sensor 4 to detect perpendicular acceleration is installed into the GPS, car-mounted computer and the like as usual, capable of detecting the horizontal acceleration. A device for detecting slope of the vehicles 1B according to the third embodiment has similar advantages to that according to the second embodiment.

Furthermore, although each embodiment differs mainly explained slope on the first embodiment, even if it uses the present invention combining the composition used for the form of not only this but each embodiment, the same action effect is acquired.

As set forth above, the advantages of the invention are as follows:

(1) The slope detecting device includes means for detecting a horizontal acceleration, mounting on a vehicle, detecting the acceleration of the running

direction of the vehicle; means for detecting perpendicular acceleration to the running direction of the horizontal detecting means; and means for detecting, attaching relatively to the horizontal detecting means and perpendicular detecting means, detecting the acceleration-deceleration the vehicle by whether the sum of
5 squares respectively which the acceleration detected by the horizontal detecting means and the acceleration detected by the perpendicular detecting means is equal to the second power of gravity acceleration, and calculating the slope of the vehicle in acceleration-deceleration so that the slope of the vehicle can be correctly detected through the slope calculation table of the detecting means based on the
10 detected acceleration so that the slope of the vehicle is correctly measured corresponding to the acceleration-deceleration during it passes through the two-level crossing etc. for example.

(2) As discussed above, since it has a simple structure, it can be carried out easily, and it can install at a high value.

15 (3) As discussed above, the slope calculation that is suitable for each situation can be performed efficiently during the uniform operation or acceleration-deceleration operation.

(4) As discussed above, also claims 2 is acquired with the same action and effect as the above (1) to (3).

20